



## TECHNICAL DATA

### FIBER-INFUSED SILICONE SEALANT

## CRAZY CAULK

#### PRODUCT DESCRIPTION

**Crazy Caulk** (patent pending) is a fiber-infused moisture-curing silicone sealant with excellent adhesion to most roof surfaces. **Crazy Caulk** is a component of the **Crazy Seal**<sup>®</sup> monolithic silicone system.

#### RECOMMENDED USES

**Crazy Caulk** makes an excellent sealant for seams. **Crazy Caulk** can be applied to rubber/EPDM, TPO, fiberglass, metal or wood.

#### COLOR AND PACKAGING

White, Tan, Gray  
11 oz. tube, 1 Gallon

#### STORAGE AND SPILLAGE INSTRUCTIONS

Store in a well ventilated place. Keep cool. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

#### PRIMING

**Crazy Caulk** will adhere to most surfaces without a primer; however, some substrates may require a primer for optimal adhesion. To verify proper adhesion, an adhesion test should be performed on a properly prepared and representative area of the substrate to be coated.

#### SURFACE PREPARATION

It is extremely important for the roof to be clean and dry before **Crazy Caulk** is applied to the weathered surface. Apply **Crazy Clean** according to label instructions.

#### APPLICATION INSTRUCTIONS

Use a standard caulk gun if tube purchased. If 1 gallon purchased, stir slowly before application to ensure uniform color and consistency. Product should not be thinned. Apply by trowel in a thin, uniform application. Do not apply in temperatures below freezing, above 120°F (49°C) or if rain is expected within 2 hours.

#### CLEAN UP & MAINTENANCE

Application tools can be cleaned with 100% pure Mineral Spirits. DO NOT USE WATER OR RECLAIMED SOLVENTS. Once a container of **Crazy Caulk** is opened, the curing process has started. Use the entire product on your project if possible. Allow any remaining product in the container to solidify and dispose of in the proper manner.

Only coat **Crazy Caulk** with **Crazy Seal**<sup>®</sup>. Other products, even silicones, are not compatible and will not stick to cured **Crazy Seal**<sup>®</sup> products.

#### PRECAUTIONS

Vapors may ignite explosively. Keep away from heat, hot surfaces, sparks and open flames. No smoking. Keep container tightly closed.

#### LIMITATIONS

Technical data is true and accurate at date of issuance, but subject to change without notice. Our products conform to **Crazy Seal**<sup>®</sup> quality standards, but no other warranty or guarantee is expressed or implied. Liability, if any, is limited to replacement of product. Labor, cost of labor or other consequential damages is hereby excluded.