



TECHNICAL DATA

FIBER-INFUSED SILICONE MASTIC

CRAZY PATCH

PRODUCT DESCRIPTION

Crazy Patch (patent pending) is a fiber-infused moisture-curing silicone mastic with excellent adhesion to most roof surfaces. **Crazy Patch** is a component of the **Crazy Seal**[®] monolithic silicone system.

RECOMMENDED USES

Crazy Patch makes an excellent sealant for penetrations. **Crazy Patch** can be applied to fiberglass, rubber/EPDM, TPO, metal or wood. **Crazy Patch** can also be used alone as a single component repair product to patch leaks.

COLOR AND PACKAGING

White, Tan, Gray
1 Gallon

STORAGE AND SPILLAGE INSTRUCTIONS

Store in a well ventilated place. Keep cool. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

PRIMING

Crazy Patch will adhere to most surfaces without a primer; however, some substrates may require a primer for optimal adhesion. To verify proper adhesion, an adhesion test should be performed on a properly prepared and representative area of the substrate to be coated.

SURFACE PREPARATION

It is extremely important for the roof to be clean and dry before **Crazy Patch** is applied to the weathered surface. Apply **Crazy Clean** according to label instructions.

APPLICATION INSTRUCTIONS

Stir slowly before application to ensure uniform color and consistency. Product should not be thinned. Apply by brush or trowel in a thin, uniform application. Do not apply in temperatures below freezing, above 120°F (49°C) or if rain is expected within 2 hours.

CLEAN UP & MAINTENANCE

Application tools can be cleaned with 100% pure Mineral Spirits. DO NOT USE WATER OR RECLAIMED SOLVENTS. Once a container of **Crazy Patch** is opened, the curing process has started. Use the entire product on your project if possible. Allow any remaining product in the container to solidify and dispose of in the proper manner.

Only coat **Crazy Patch** with **Crazy Seal**[®]. Other products, even silicones, are not compatible and will not stick to cured **Crazy Seal**[®] products.

PRECAUTIONS

Vapors may ignite explosively. Keep away from heat, hot surfaces, sparks and open flames. No smoking. Keep container tightly closed.

LIMITATIONS

Technical data is true and accurate at date of issuance, but subject to change without notice. Our products conform to **Crazy Seal**[®] quality standards, but no other warranty or guarantee is expressed or implied. Liability, if any, is limited to replacement of product. Labor, cost of labor or other consequential damages is hereby excluded.