



## TECHNICAL DATA

# FIBER-INFUSED SILICONE ROOF MEMBRANE

### PRODUCT DESCRIPTION

**Crazy Seal**® (patent pending) is a premium, fluid-applied, fiber-infused silicone roof membrane. Applying **Crazy Seal**® to any weathered roof substrate will help ensure it is protected against degradation caused by harsh UV rays, severe weather, mold and mildew. It will not chalk or blister. The unique fiber-infused silicone makeup of **Crazy Seal**® remains permanently flexible yet strong.

### PRODUCT ADVANTAGES

- High reflective properties help reduce interior temperature and A/C expense
- Dries into a seamless, maintenance free waterproof monolithic membrane
- Extremely light so it will not add stress to your roof or chassis
- Fiber-infusion makes it scratch resistant, strong and tough
- Designed to be puncture and tear resistant
- Won't crack, chip, peel or streak
- Resistant to mold penetration, fungus, salt, acids and is chemically resistant

### RECOMMENDED USES

**Crazy Seal**® can be applied to fiberglass, rubber/EPDM, TPO, metal or wood. **Crazy Seal**® can be used on virtually all low slope roof applications. The **Crazy Seal**® system is compatible with all types of RV's, motorhomes, 5<sup>th</sup> wheels, travel trailers, pop-ups, park models and semi-trailers.

### COLOR AND PACKAGING

White, Tan, Gray  
1 Gallon, 3 Gallon, 5 Gallon

### STORAGE AND SPILLAGE INSTRUCTIONS

Store in a well ventilated place. Keep cool. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

### PRIMING

**Crazy Seal**® will adhere to most surfaces without a primer; however, some substrates may require a primer for optimal adhesion. To verify proper adhesion, an adhesion test should be performed on a properly prepared and representative area of the substrate to be coated.

### SURFACE PREPARATION

It is extremely important for the roof to be clean and dry before **Crazy Seal**® is applied to the weathered surface. Apply **Crazy Clean** according to label instructions.

### APPLICATION INSTRUCTIONS

(Minimum requirement) Mix slowly before application to ensure uniform color and consistency. Product should not be thinned. Use a solvent-resistant roller. Dip roller directly into pail and apply, or pour product onto the flat roof surface and roll out evenly. The coverage rate of **Crazy Seal**® is 1 gallon per 100 sq. ft. Coverage rate may decrease on heavily textured or weathered roofs. Allow to dry for 4 to 12 hours. Do not apply in temperatures below freezing, above 120°F (49°C) or if rain is expected within 2 hours. Light foot traffic is allowed for equipment servicing only.

### CLEAN UP & MAINTENANCE

Application tools and equipment can be cleaned with 100% pure Mineral Spirits. DO NOT USE WATER OR RECLAIMED SOLVENTS. Once a container of **Crazy Seal**® is opened, the curing process has started. Use the entire product on your project if possible. Allow any remaining product in the container to solidify and dispose of in the proper manner. Roof structures may settle over time. A periodic inspection of your roof, which includes transition areas, vents, sanitary pipes or skylights, is recommended.

**Crazy Seal Products, Inc.**  
[www.crazyseal.com](http://www.crazyseal.com)

Roofs become slippery when wet. Use extreme caution. When the roof is finished, best safety practices should be followed. If it is necessary to be on the roof, it is best to do so on a dry, sunny day. It is advised not to walk on a wet roof, but if you must do so wearing aggressive-tread shoes or boots is recommended.

Only recoat with **Crazy Seal®**. Other products, even silicones, are not compatible and will not stick to cured **Crazy Seal®**.

### **CAUTION**

An old, neglected or failing roof does not have the resilience to withstand the rigors of weather. **Crazy Seal®** may not be suitable for such a roof. If you are in doubt about the condition of your roof, consult a qualified inspector. Note: **Crazy Seal®** is the final step in creating a monolithic roof membrane and is not suitable as a standalone patch.

### **PRECAUTIONS**

Vapors may ignite explosively. Keep away from heat, hot surfaces, sparks and open flames. No smoking. Keep container tightly closed.

### **LIMITATIONS**

Technical data is true and accurate at date of issuance, but subject to change without notice. Our products conform to **Crazy Seal®** quality standards, but no other warranty or guarantee is expressed or implied. Liability, if any, is limited to replacement of product. Labor, cost of labor or other consequential damages is hereby excluded.