



TECHNICAL DATA

SEAM SEALING TAPE

CRAZY TAPE

PRODUCT DESCRIPTION

Crazy Tape is a laminate of a proprietary adhesive/sealant and a high-strength stitch bonded polyester fabric. The adhesive/sealant is a patented, cured butyl-based permanently pressure-sensitive material.

RECOMMENDED USES

Crazy Tape is used to seal seams and edges on roof decks. Extremely flexible, with no memory, **Crazy Tape** conforms to virtually any shape.

BENEFITS

- Fast easy installation
- Excellent conformability
- Proven technology and durability
- An unusual combination of high strength properties with good elongation for excellent thermal stress force accommodation
- Excellent heat, water and chemical resistance
- Excellent short and long term strength over a broad temperature range
- VOC compliant
- Adhesive displays very high tack, peel and shear strengths

COLOR AND PACKAGING

Charcoal Gray
Roll size is 4" x 25 foot

Crazy Tape is supplied on a high strength, specially-formulated release paper.

STORAGE INSTRUCTIONS

Protect against weather until installed.

APPLICATION INSTRUCTIONS

It is important for the roof to be clean and dry. Apply **Crazy Tape** to seams and edges. Be sure to straddle seams on both sides to promote good adhesion. Be careful with **Crazy Tape** because the adhesive is incredibly strong.

PRECAUTIONS

Aggressively adheres. Do not stretch tape during installation. Properly dispose of release paper.

LIMITATIONS

Technical data is true and accurate at date of issuance, but subject to change without notice. Our products conform to **Crazy Seal**® quality standards, but no other warranty or guarantee is expressed or implied. Liability, if any, is limited to replacement of product. Labor, cost of labor or other consequential damages is hereby excluded.